

Painting over wallpaper (in good condition)





Interior walls

Painting over wallpaper (in good condition)

Notes:

- Wallpaper in good condition is easy to paint but once painted, the wallpaper will be more difficult to remove.
- Some vinyl wallpapers will allow migration of plasticisers into the paint film and this will result in the paint remaining slightly sticky or tacky. Typically if a testpot is used during the colour selection process and it doesn't get tacky then our other coatings will also be fine. However it can take upwards of three weeks for this tackiness to become apparent.



- Use Resene Vinyl Wallpaper Sealer over solid and paperbacked vinyl wallpapers.
- Very occasionally you may have an otherwise sound paper with a metallic printed pattern. This will need sealing with Resene Sureseal or Resene Enamel Undercoat prior to painting.



- Some edges may need sticking down and this is best done with Selleys Aquadhere PVA glue applied to both faces, left for at least 20 minutes and firmly pressed or rolled flat.
- Small bubbles, often only apparent after the first coat of paint, may be cross cut with a sharp blade and the edges glued down.



- When stopping holes in wallpaper press in the surrounds with the handle of a putty knife prior to stopping the hole, otherwise you may be left with a lump on the surface.
- You may find the junction of the skirting and wall difficult to cut in because papers usually slightly overlay the junction and a relatively ragged edge results.
 Often it is best to paint the skirting board and the wall the same colour for the most even finish.

Key accessories essential to complete the job

- 220 grit zinc stearate sandpaper
- Resene Vinyl Wallpaper Sealer
- Selleys Rapid Filla

Add-ons - to make the job easier or quicker

- Dropsheet
- Masking tape
- Resene Enamel Undercoat if required
- Resene Sureseal if required
- Turps

