Resene

Wooden picture frame



★★ Difficulty level ★easy ★★moderate ★★★challenging

The second of the second secon

to be the production of the state of the sta

Ways with wood with Mark Rayner - 76

You will need:

- Clean cloths
- Old wooden picture frame
- Mineral turpentine for cleaning brush
- Paintbrush

- Pliers
- Resene Danska Teak Oil
- Rubber gloves
- Sandpaper



Step one

Remove the backing board hanging and device from the picture frame.



Step two

Carefully pull out any framing staples with pliers and remove the



Step three

Remove any old framing tape from the back of the picture frame.



Step four

Sand the back of the picture frame to remove any old gum residue from the framing tape.



Step five

Carefully sand the front of the picture frame with a medium grade sandpaper. Wipe clean and then finish off with a fine grade sandpaper.



Step six

Wipe off any sanding residue with a clean cloth.



Step seven

Apply one coat of Resene Danska Teak Oil to the picture frame, brushing in the direction of the grain.



Step eight

Wipe off any excess Resene Danska Teak Oil with a clean cloth and allow 24 hours to dry. Clean brush with mineral turpentine.



It's easy to transform an old wooden picture frame using Resene Danska Teak Oil.



To get the look:

Mark painted the background wall with Resene SpaceCote Flat tinted to Resene Picton Blue.



Other ideas:

For a paler effect, an old wooden picture frame can also be transformed using **Resene Colorwood** Whitewash.

For more ideas and inspiration visit your local Resene ColorShop or www.resene.com/ colorshops.

Check out more project ideas online www.resene.com/projects.



the paint the professionals use