

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.

Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene Stone Strengthener

A-LL8520004 7/16

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Harmful if inhaled. Causes mild skin irritation. Causes serious eye irritation. May cause damage to organs. Harmful to aquatic life with long lasting effects. Harmful to terrestrial vertebrates.

PRECAUTIONS

DO NOT BREATHE DUST, FUMES, GAS, MISTS, VAPOURS, SPRAYS. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Store locked up. Use only outdoors or in a well ventilated area. Wear protective gloves and clothing, eye and face protection. Avoid release to the environment. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

FIRST AID

IF SWALLOWED: Immediately call a POISON CENTRE, doctor, physician or first aider.

IF ON SKIN (or hair): Remove all contaminated clothing and wash before reuse. Wash skin with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention or advice.

INHALATION: Remove to fresh air. IF BREATHING DIFFICULT GET MEDICAL ATTENTION IMMEDIATELY.

If exposed or you feel unwell. Call a POISON CENTRE, doctor or physician. When seeking medical advice take this container with you.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

CONTAINS: Dibutyltin Dilurate 1-10 gms/L, Tetraethyl silicate 100-220 gms/L. For use as a decorative/protective coating.

For full technical instructions see Data Sheet D904.

SPILLS: Eliminate all sources of ignition and use appropriate protective equipment. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with the recommended thinner. Do not allow thinner to enter any drains. Refer to your local Council for disposal of dirty thinner.

FIRE: Use CO₂, dry powder or foam to extinguish.

Use on: Sandstone, Oamaru stone, weathered bricks, lightweight concrete, weathered plasters.

Typical coverage: 1-10 square metres per litre depending on surface.

Dry time (minimum): Can be used immediately after application.

Recoat time (minimum): Dependant on substrate and application conditions.

Usual number of coats: One.

Thinning and clean up: Do not thin. Clean up with mineral turps.

Before use: Stir well with a wide flat stirrer.

Pot life: One year in full sealed containers.

Performance

- Reinforces weak substrates with inert, acid-resistant silica gel.

- Negligible change in surface appearance.
- Low molecular weight for optimum penetration.

Precautions and limitations

- Releases ethyl alcohol – use only in well ventilated areas.

- Will etch glass. Protect window glass.

- Excess material left on the surface should be removed with mineral turps if still wet or ammonia if dried. Remove unabsorbed material.

- Wear protective gloves and goggles.

- Will gel in contact with moisture – rinse spray equipment thoroughly with water.

Surface preparation

- Surfaces to be treated should be clean and dry.

Application

- Flood surfaces with low pressure spray application.

- Some very porous surfaces will take large amounts of Resene Stone Strengthener. The degree of strengthening required should be determined and a suitable application rate established.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

net contents 4 litres



COMBUSTIBLE LIQUID

Keep away from heat, sparks, open flames and hot surfaces. No smoking.



Stone Strengthener SDS

Resene

the paint the professionals use



Stone Strengthener TDS

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAJ, an accredited certification body. This product complies with all the requirements of an APAS Paint Specification. Refer to the APAS Specification list on the Resene website for full details. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

